

Printing date 06/22/2009

Reviewed on 02/25/2009

1 Identification of substance

- **Product details**
- **Trade name:** *Acryl-Haftgrund Spray*
- **Application of the substance / the preparation** *Priming*
- **Manufacturer/Supplier:**
MIPA AG
Am Oberen Moos 1
D-84051 Essenbach
Tel.: 0049(0) 8703-922-0
Fax.: 0049(0) 8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Information department:** *Laboratory*
- **Emergency information:** *011 49(0)5262-9939657 (MIP)*

2 Composition/Data on components

- **Chemical characterization**
- **Description:** *Mixture of the substances listed below with nonhazardous additions.*

- **Dangerous components:**

67-64-1	acetone	25-50%
123-86-4	n-butyl acetate	10-25%
74-98-6	propane	2.5-10%
106-97-8	butane	2.5-10%
7779-90-0	trizinc bis(orthophosphate)	≤ 2.5%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	≤ 2.5%
67-63-0	propan-2-ol	≤ 2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤ 2.5%

3 Hazards identification

- **Hazard description:**



Irritant
Extremely flammable

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Warning! Pressurized container.
Has a narcotizing effect.
Extremely flammable.
Irritating to eyes.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
Buildup of explosive mixtures possible without sufficient ventilation.
Keep out of the reach of children.

(Contd. on page 2)

USA

Printing date 06/22/2009

Reviewed on 02/25/2009

Trade name: Acryl-Haftgrund Spray

(Contd. of page 1)

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 4

Reactivity = 3

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1
FIRE	4
REACTIVITY	3

Health = 1

Fire = 4

Reactivity = 3

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- **Person-related safety precautions:**
Ensure adequate ventilation
Keep away from ignition sources
Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Dispose of the collected material according to regulations.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.

(Contd. on page 3)

Printing date 06/22/2009

Reviewed on 02/25/2009

Trade name: Acryl-Haftgrund Spray

(Contd. of page 2)

- **Information about protection against explosions and fires:**
Fumes can combine with air to form an explosive mixture.
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not gas tight seal receptacle.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	2400 mg/m ³ , 1000 ppm
REL	590 mg/m ³ , 250 ppm
TLV	Short-term value: 1782 mg/m ³ , 750 ppm Long-term value: 1188 mg/m ³ , 500 ppm
BEI	

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

74-98-6 propane

PEL	1800 mg/m ³ , 1000 ppm
REL	1800 mg/m ³ , 1000 ppm
TLV	Varies mg/m ³ , 1000 ppm

106-97-8 butane

REL	1900 mg/m ³ , 800 ppm
TLV	Varies mg/m ³ , 1000 ppm

67-63-0 propan-2-ol

PEL	980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm
BEI	

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 4)

USA

Printing date 06/22/2009

Reviewed on 02/25/2009

Trade name: Acryl-Haftgrund Spray

(Contd. of page 3)

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Do not eat, drink, smoke or sniff while working.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Light weight protective clothing

9 Physical and chemical properties

· General Information

Form: Aerosol
Color: According to product specification
Odor: Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: -44°C (-47°F)

· **Flash point:** < 0°C (< 32°F) (DIN 53213)

· **Ignition temperature:** 365°C (689°F) (DIN 51794)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol %
Upper: 13.0 Vol %

· **Vapor pressure at 20°C (68°F):** 8300 hPa (6226 mm Hg)

(Contd. on page 5)

Printing date 06/22/2009

Reviewed on 02/25/2009

Trade name: Acryl-Haftgrund Spray

(Contd. of page 4)

- | | |
|--|------------------------------------|
| · Density at 20°C (68°F): | 0.89 g/cm ³ (DIN 53217) |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Solvent separation test | < 3 % |
| · Solvent content: | |
| Organic solvents: | 81.8 % |
| VOC content: | 41.5 % |
| | 792.7 g/l / 6.62 lb/gl |
| · Solids content (weight-%): | 17.2 % |

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous products of decomposition:** Carbon monoxide

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

12 Ecological information

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

13 Disposal considerations

· **Product:**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)

Printing date 06/22/2009

Reviewed on 02/25/2009

Trade name: *Acryl-Haftgrund Spray*

(Contd. of page 5)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **DOT regulations:**



- **Hazard class:** 2.1
- **Identification number:** UN1950
- **Packing group:** -
- **Hazardous substance:** 1950 lbs, 885 kg
- **Proper shipping name (technical name):** AEROSOLS, flammable
- **Label:** 2.1

· **Land transport ADR/RID (cross-border):**



- **ADR/RID class:** 2 5F Gases
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Label:** 2.1
- **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



- **IMDG Class:** 2
- **UN Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Propper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label:** 2.1
- **Packaging group:** -

(Contd. on page 7)

Printing date 06/22/2009

Reviewed on 02/25/2009

Trade name: **Acryl-Haftgrund Spray**

(Contd. of page 6)

 · **Propper shipping name:** AEROSOLS, flammable

15 Regulations

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

67-63-0 | propan-2-ol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1 | acetone

I

· IARC (International Agency for Research on Cancer)

67-63-0 | propan-2-ol

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 | acetone

A4 25-50%

67-63-0 | propan-2-ol

A4 ≤2,5%

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:

Irritant

Extremely flammable

· Risk phrases:

Extremely flammable.

Irritating to eyes.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

(Contd. on page 8)

Printing date 06/22/2009

Reviewed on 02/25/2009

Trade name: Acryl-Haftgrund Spray

(Contd. of page 7)

Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Keep in a cool place.

Keep container in a well-ventilated place.

Do not breathe aerosol.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

· Special labeling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children.

· National regulations:

· Information about limitation of use:

None of the ingredients is listed.

Class	Share in %
NK	50-100

*** 16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: MIPA AG, Abteilung Umweltschutz

· Contact: Michaela Knall

· * Data compared to the previous version altered.

USA