

1 Identification of substance

· **Product details**

- **Trade name:** Aktivprimer
- **Application of the substance / the preparation:** Primer

· **Manufacturer/Supplier:**

MIPA AG
Am Oberen Moos 1
D-84051 Essenbach
Tel.: 0049(0) 8703-922-0
Fax.: 0049(0) 8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com

· **Information department:** Laboratory

· **Emergency information:**

011 49(0)5262-9939657 (MIP)
US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

2 Composition/Data on components

· **Chemical characterization**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1330-20-7	xylene	25-50%
71-36-3	butan-1-ol	10-25%
64-17-5	ethanol	10-25%
25036-25-3	bisphenole	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
7779-90-0	Preparation based on zincphosphate (supplier's classification)	2.5-10%

3 Hazards identification

· **Hazard description:**



Harmful

· **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

Flammable.

Harmful by inhalation and in contact with skin.

Irritating to skin.

Risk of serious damage to eyes.

May cause sensitisation by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: Aktivprimer

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

4 First aid measures· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*· **After eye contact:** *Rinse opened eye for several minutes under running water. Then consult a doctor.*· **After swallowing:** *If symptoms persist consult doctor.***5 Fire fighting measures**· **Suitable extinguishing agents:** *CO₂, sand, extinguishing powder. Do not use water.*· **For safety reasons unsuitable extinguishing agents:** *Water with full jet*· **Protective equipment:** *Mouth respiratory protective device.***6 Accidental release measures**· **Person-related safety precautions:** *Wear protective equipment. Keep unprotected persons away.*· **Measures for environmental protection:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage· **Handling:**· **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Storage:**· **Requirements to be met by storerooms and receptacles:** *No special requirements.*· **Information about storage in one common storage facility:** *Store away from foodstuffs.*· **Further information about storage conditions:** *Keep receptacle tightly sealed.*

USA

(Contd. on page 3)

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: Aktivprimer

(Contd. of page 2)

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

1330-20-7 xylene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm
BEI	

71-36-3 butan-1-ol

PEL	300 mg/m ³ , 100 ppm
REL	Short-term value: C 150 mg/m ³ , C 50 ppm Skin
TLV	61 mg/m ³ , 20 ppm

64-17-5 ethanol

PEL	1900 mg/m ³ , 1000 ppm
REL	1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , NIC-1000 ppm Long-term value: 1880 mg/m ³ , 1000 ppm NIC-A3

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

(Contd. on page 4)

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: Aktivprimer

(Contd. of page 3)

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	78°C (172°F)

· **Flash point:** 24°C (75°F) (DIN 53213)

· **Ignition temperature:** 340°C (644°F) (DIN 51794)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	1.1 Vol %
Upper:	15.0 Vol %

· **Vapor pressure at 20°C (68°F):** 59 hPa (44 mm Hg)

· **Density at 20°C (68°F):** 0.985 g/cm³ (DIN 53217)

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Viscosity:**

Kinematic at 20°C (68°F): 75 s (DIN 53211/4)

· **Solvent separation test** < 3 %

· **Solvent content:**

Organic solvents:	66.6 %
Water:	0.8 %
VOC content:	66.6 %
	less exempt solvents 656.6 g/l / 5.48 lb/gl
	with exempt solvents 661.7 g/l / 5.52 lb/gl

· **Solids content (weight-%):** 32.6 %

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 5)

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: Aktivprimer

(Contd. of page 4)

- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** Carbon monoxide

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
------	------	------------------

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful
Irritant

12 Ecological information

- **Ecotoxicological effects:**

- **Aquatic toxicity:**

7779-90-0 Preparation based on zincphosphate (supplier's classification)

EC50	63.1 mg/kg (daphnia)
------	----------------------

- **Remark:** Harmful to fish
- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

13 Disposal considerations

- **Product:**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 6)

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: Aktivprimer

(Contd. of page 5)

14 Transport information

· **DOT regulations:**



- **Hazard class:** 3
- **Identification number:** UN1263
- **Packing group:** III
- **Proper shipping name (technical name):** PAINT
- **Label:** 3

· **Land transport ADR/RID (cross-border):**



- **ADR/RID class:** 3 (F1) Flammable liquids
- **Danger code (Kemler):** 30
- **UN-Number:** 1263
- **Packaging group:** III
- **Label:** 3
- **Description of goods:** 1263 PAINT, special provision 640E

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1263
- **Label:** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Propper shipping name:** PAINT

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label:** 3
- **Packaging group:** III
- **Propper shipping name:** PAINT

USA

(Contd. on page 7)

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: Aktivprimer

(Contd. of page 6)

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
-----------	--------

71-36-3	butan-1-ol
---------	------------

78-93-3	butanone
---------	----------

100-41-4	Ethylbenzene
----------	--------------

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
---------	---------

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
-----------	--------	---

71-36-3	butan-1-ol	D
---------	------------	---

78-93-3	butanone	I
---------	----------	---

1314-13-2	zinc oxide	II
-----------	------------	----

100-41-4	Ethylbenzene	D
----------	--------------	---

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
-----------	--------	---

14807-96-6	Talk	3
------------	------	---

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4	25-50%
-----------	--------	----	--------

64-17-5	ethanol	A4	10-25%
---------	---------	----	--------

14807-96-6	Talk	A4	2,5-10%
------------	------	----	---------

100-41-4	Ethylbenzene	A3	≤2,5%
----------	--------------	----	-------

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 8)

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: Aktivprimer

(Contd. of page 7)

· Hazard symbols:*Harmful***· Hazard-determining components of labelling:***bisphenole**xylene***· Risk phrases:***Flammable.**Harmful by inhalation and in contact with skin.**Irritating to skin.**Risk of serious damage to eyes.**May cause sensitisation by skin contact.**Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.***· Safety phrases:***Keep out of the reach of children.**Do not breathe fumes/aerosol.**In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.**Wear suitable protective clothing, gloves and eye/face protection.**If swallowed, seek medical advice immediately and show this container or label.**Use only in well-ventilated areas.***· National regulations:****· Information about limitation of use:**

64-17-5	ethanol	5
14807-96-6	Talk	3B
100-41-4	Ethylbenzene	3A

Class	Share in %
NK	50-100

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: MIPA AG, Abteilung Umweltschutz

· Contact: Michaela Knall

· * Data compared to the previous version altered.

USA