

1 Identification of substance

· Product details

- **Trade name:** *BC-Verdünnung lang / BC-Thinner long*
- **Application of the substance / the preparation** *Thinner, Diluent*

· Manufacturer/Supplier:

MIPA AG
 Am Oberen Moos 1
 D-84051 Essenbach
 Tel.: 0049(0) 8703-922-0
 Fax.: 0049(0) 8703-922-100
 e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com

· Information department: Laboratory

· Emergency information:

011 49(0)5262-9939657 (MIP)
 US Emergency Telephone Number (for transportation incidents only): 1-800-535-5053 (Infotrac)

2 Composition/Data on components

· Chemical characterization

- **Description:** *Mixture of the substances listed below with nonhazardous additions.*

· Dangerous components:

64742-95-6	Solvent naphtha (petroleum), light arom.	25-50%
123-86-4	n-butyl acetate	25-50%
112-07-2	2-butoxyethyl acetate	2.5-10%

3 Hazards identification

· Hazard description:



Harmful
Dangerous for the environment

· Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Has a narcotizing effect.
Flammable.
Irritating to respiratory system.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Harmful: may cause lung damage if swallowed.
Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



Health = 1
Fire = 3
Reactivity = 0

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: BC-Verdünnung lang / BC-Thinner long

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

* 7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

* 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 3)

USA

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: BC-Verdünnung lang / BC-Thinner long

(Contd. of page 2)

· Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

112-07-2 2-butoxyethyl acetate

REL	33 mg/m ³ , 5 ppm Skin
TLV	130 mg/m ³ , 20 ppm

· Additional information: The lists that were valid during the creation were used as basis.

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 124°C (255°F)

(Contd. on page 4)

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: BC-Verdünnung lang / BC-Thinner long

(Contd. of page 3)

· Flash point:	28°C (82°F) (DIN 53213)
· Ignition temperature:	280°C (536°F) (DIN 51794)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20°C (68°F):	10.7 hPa (8 mm Hg)
· Density at 20°C (68°F):	0.879 g/cm ³ (DIN 53217)
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Viscosity:	
Kinematic at 20°C (68°F):	11 s (DIN 53211/4)
· Solvent separation test	< 3 %
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.0 %
	879.2 g/l / 7.34 lb/gal

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous products of decomposition:** Carbon monoxide

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>3400 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4 h	>10.2 mg/l (rat)
------------	----------	------------------

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish

(Contd. on page 5)

USA

Printing date 04/29/2009

Reviewed on 04/29/2009

Trade name: BC-Verdünnung lang / BC-Thinner long

(Contd. of page 4)

· **General notes:**

- *Water hazard class 2 (Self-assessment): hazardous for water*
- *Do not allow product to reach ground water, water course or sewage system.*
- *Danger to drinking water if even small quantities leak into the ground.*
- *Also poisonous for fish and plankton in water bodies.*
- *Toxic for aquatic organisms*

13 Disposal considerations

· **Product:**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **DOT regulations:**



- **Hazard class:** 3
- **Identification number:** UN1263
- **Packing group:** III
- **Proper shipping name (technical name):** PAINT RELATED MATERIAL
- **Label:** 3

· **Land transport ADR/RID (cross-border):**



- **ADR/RID class:** 3 (F1) Flammable liquids
- **Danger code (Kemler):** 30
- **UN-Number:** 1263
- **Packaging group:** III
- **Label:** 3
- **Description of goods:** 1263 PAINT RELATED MATERIAL, special provision 640E

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1263
- **Label:** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No

(Contd. on page 6)

USA

Trade name: BC-Verdünnung lang / BC-Thinner long

(Contd. of page 5)

· **Propper shipping name:** PAINT RELATED MATERIAL

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3
 · **UN/ID Number:** 1263
 · **Label:** 3
 · **Packaging group:** III
 · **Propper shipping name:** PAINT RELATED MATERIAL

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

112-07-2	2-butoxyethyl acetate	A3	2,5-10%
----------	-----------------------	----	---------

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 7)

Trade name: BC-Verdünnung lang / BC-Thinner long

(Contd. of page 6)

· Hazard symbols:

Harmful
Dangerous for the environment

· Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

· Risk phrases:

Flammable.
Irritating to respiratory system.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Harmful: may cause lung damage if swallowed.
Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.
Keep away from food, drink and animal feedingstuffs.
Do not breathe fumes/aerosol.
Avoid contact with eyes.
Wear suitable protective clothing.
If swallowed, seek medical advice immediately and show this container or label.

· National regulations:

· Information about limitation of use:

112-07-2	2-butoxyethyl acetate	4
----------	-----------------------	---

Class	Share in %
NK	50-100

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS:** MIPA AG, Abteilung Umweltschutz
- **Contact:** Michaela Knall
- * **Data compared to the previous version altered.**